

Heartwood LVT

Product Specifications

Style Name	Heartwood LVT
Style Number	I436V
Construction	LVT
Wear Layer Thickness	20 mil (.020"/.5 mm)
Overall Thickness	.098" (2.5 mm)
Reference Specification	Class III printed film vinyl plank
ASTM F 1700	Type B (embossed)
Finish	ExoGuard+™
Installation	Glue Down
Recommended Adhesive	Shaw 4100 or S150

Packaging

Plank Size	5.96" W x 48" L
Pieces/Box	21
Sq. Ft./Box	41.72


Performance Testing

Commercial Traffic Class	Heavy
Static Load/ASTM F970	Passes, Modified – 1500 psi
Residual Indentation/ASTM 1914	Passes
Dimensional Stability/ASTM F2199	Passes
Flexibility/ASTM F 137	Passes
Resistance to Heat/ASTM F 1514	Passes
Resistance to Light/ASTM F 1515	Passes
Resistance to Chemicals/ASTM 925	Passes
Radiant Flux/ASTM E 648	Class I
Smoke Density/ASTM E 662	<450, Passes

Warranty

Lifetime Commercial Limited Warranty.
 10 Year Underbed Warranty when installed with 4100 or S150 adhesive.
 Please visit patcraft.com for the most current warranty information.

Installation Methods



Environmental

FloorScore Certified